

NEW

Ken-Tool®
WHEREVER TIRES ARE CHANGED™



T112 12-BAR EARTHMOVER TIRE INFLATION CAGE

Mandatory for any shop working with tubeless and multi-piece rims. Guards against blown lock rings and rims. Designed to meet OSHA reg. 29-CFR Part 1910.177.



36012 - Patented

Ken-Tool Introduces the T112 12-Bar Earthmover Tire Inflation Cage

- For large Earthmover & Agricultural and Mining tires
- New fully patented design; with 12-bar construction
- Fits tires and wheels 87" total height by 48" wide
- For maximum tire inflation pressure up to 100-psi
- Cage dimensions: 80" x 60" x 99.5"; ships by flatbed truck only
- T111 explosion testing video at 150-psi on www.kentool.com
- Full cage line is proudly Made in USA



36001 / 36007

36002

36003

36004

36005

36006

36008


36011

NEW

Item No.	Height A	Width B	Base	Weight
36012 (T112)	87" (221 cm)	48" (122 cm)	60" x 80" (152 cm x 213 cm)	1200 lbs (545 kg)
36001 (T101)	41" (104 cm)	16" (41 cm)	7" closed x 21½" (18 cm x 55 cm)	60 lbs (27.2 kg)
36007 (T101A)	43½" (111cm)	20½" (52 cm)	7" closed x 27" (18 cm x 69 cm)	72 lbs (32.6 kg)
36002 (T102)	43½" (111cm)	20½" (52 cm)	31½" x 26" (80 cm x 66 cm)	146 lbs (66.2 kg)
36003 (T103)	30" (76 cm)	16" (41 cm)	21½" x 22" (55 cm x 56 cm)	80 lbs (36.2 kg)
36004 (T104)	65" (165 cm)	24" (61 cm)	30" x 27" (76 cm x 69 cm)	158 lbs (72.6 kg)
36005 (T105)	43½" (111cm)	20½" (52 cm)	41" x 26" (104 cm x 66 cm)	182 lbs (82.5 kg)
36006 (T106)	43½" (111cm)	20½" (52 cm)	26" x 22 (66 cm x 56 cm)	134 lbs (60.7 kg)
36008 (T108)	46" (117 cm)	29" (74 cm)	34" x 56 (86 cm x 142 cm)	485 lbs (220 kg)
36011 (T111)	76" (193 cm)	42" (107 cm)	48" x 72" (122 cm x 183 cm)	820 lbs (371.9 kg)
36014 (T114)	EZ TIRE ROTATOR (Patent Pending)		17½" x 25½" x 2½"	19 lbs (8.6 kg)



36014



*Work safely.
Always use an inflation cage when inflating tires.
Follow OSHA regulation 29-CFR Part 1910.177 whenever changing tires.*

KEN-TOOL • 768 E. North Street • Akron, OH 44305
Toll Free: 888-536-8665 • Fax: 800-872-4929 • Phone: 330-535-7177 • Fax: 330-535-1345
E-mail: sales@kentool.com • www.kentool.com

KT100716-EB